according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Abra-CLEAN

 Revision date :
 25.01.2016
 Version :
 1.0.0

 Print date :
 03.02.2016
 Page :
 1/9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Lithofin Abra-CLEAN

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Mixture Washing and cleaning products, contains: organic solvents alkaline

1.3 Supplier (manufacturer/importer/only representative/downstream user/distributor)

Distributor : CDK Stone Pty Ltd Street : 4-6 Freighter Rd

Postal code/city: AUS-Moorabbin, Victoria 3189

 Telephone :
 +61 3 8552-6000

 Telefax :
 +61 3 8552-6001

 Contact :
 Technical Department

E-mail: enquiries@cdkstone.com.au

Emergency telephone number:

+61 (0)3 8552-6000

(Only available during office hours)

Supplier: Lithofin AG

 Street :
 Heinrich-Otto-Str. 36

 Postal code/city :
 73240 Wendlingen

 Telephone :
 +49 (0)7024 9403-0

 Telefax :
 +49 (0)7024 9403-40

1.4 Emergency telephone number

see section 1.3

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Eye Dam. 1; H318 - Serious eye damage/eye irritation: Category 1; Causes serious eye damage. Skin Irrit. 2; H315 - Skin corrosion/irritation: Category 2; Causes skin irritation.

Additional information

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Remark

Full text of H- and EUH-phrases: see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Corrosion (GHS05)

Signal word

Danger

Hazard components for labelling

2-AMINOETHANOL ; CAS No. : 141-43-5

Alcohols, C12-14, ethoxylated; CAS No.: 68439-50-9

Hazard statements

H318 Causes serious eye damage. H315 Causes skin irritation.

Precautionary statements

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Abra-CLEAN

 Revision date :
 25.01.2016
 Version :
 1.0.0

 Print date :
 03.02.2016
 Page :
 2 / 9

P102 Keep out of reach of children.

P280 Wear protective gloves and eye/face protection.
P337+P313 If eye irritation persists: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with

local and national regulations.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Adverse human health effects and symptoms

Due to its pH value (see section 9), irritation of the skin and eyes cannot be ruled out.

2.4 Additional information

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Hazardous ingredients

Hydrocarbons, C13-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics; REACH registration No.: 01-2119485032-45-xxxx; EC No.: 921-050-8; CAS No.: (64742-47-8)

Weight fraction : \geq 20 - < 25 % Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

2-AMINOETHANOL; REACH registration No.: 01-2119486455-28-xxxx; EC No.: 205-483-3; CAS No.: 141-43-5

Weight fraction : $\geq 3 - < 5 \%$

Classification 1272/2008 [CLP]: Skin Corr. 1B; H314 Eye Dam. 1; H318 Acute Tox. 4; H302 Acute Tox. 4; H312

Acute Tox. 4; H332 STOT SE 3; H335

Alcohols, C12-14, ethoxylated, sulfates, sodium salts; REACH registration No.: 01-2119488639-16-xxxx; EC No.: 500-234-

8; CAS No. : 68891-38-3

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP]: Eye Dam. 1; H318 Skin Irrit. 2; H315 Aquatic Chronic 3; H412

9

Weight fraction : $\geq 1 - < 3 \%$

Classification 1272/2008 [CLP]: Eye Dam. 1; H318 Aquatic Acute 1; H400

Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

After ingestion

Call a physician immediately. Keep at rest. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

Self-protection of the first aider

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Abra-CLEAN

 Revision date :
 25.01.2016
 Version :
 1.0.0

 Print date :
 03.02.2016
 Page :
 3 / 9

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water alcohol resistant foam ABC-powder Carbon dioxide (CO2) Water spray

Unsuitable extinguishing media

Full water jet Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide. Carbon dioxide (CO2)

5.3 Advice for firefighters

Use suitable breathing apparatus.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. The product itself does not burn. Coordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Suitable material for taking up: Universal binder

6.4 Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1 Precautions for safe handling

When using do not eat, drink, smoke, sniff.

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Measures to prevent fire

The product is not: Flammable Usual measures for fire prevention.

Fire class : B
Shake before use nein

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.

Hints on joint storage

Storage class (TRGS 510): 10
Protect from frost nein

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Abra-CLEAN

 Revision date :
 25.01.2016
 Version :
 1.0.0

 Print date :
 03.02.2016
 Page :
 4 / 9

Recommended storage temperature 5 - 25 °C

Further information on storage conditions

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

7.3 Specific end use(s)

Recommendation

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

2-AMINOETHANOL; CAS No.: 141-43-5

Peak limitation: 2(I)
Remark: H, Y, Sh
Version: 02.04.2014
Limit value type (country of origin): STEL (EC)

Limit value: 3 ppm / 7,6 mg/m³ Remark: H

Version: 07.02.2006
Limit value type (country of origin): TWA (EC)

Limit value: 1 ppm / 2,5 mg/m³

Remark: H Version: 06.02.2008

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL Consumer (systemic) (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ;

CAS No.: 68891-38-3)

Exposure route: Oral

Exposure frequency : Long-term (repeated)

Limit value : 15 mg/kg/d

Limit value type : DNEL Consumer (systemic) (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ;

CAS No.: 68891-38-3)

Exposure route : Dermal

Exposure frequency: Long-term (repeated)
Limit value: 1650 mg/kg/d

Limit value type: DNEL Consumer (systemic) (Alcohols, C12-14, ethoxylated, sulfates, sodium salts;

CAS No.: 68891-38-3)

Exposure route : Inhalation

Exposure frequency: Long-term (repeated)

Limit value: 52 mg/m³

Limit value type : DNEL worker (systemic) (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ; CAS

No.: 68891-38-3)

Exposure route : Dermal

Exposure frequency: Long-term (repeated)
Limit value: 2750 mg/kg/d

Limit value type : DNEL worker (systemic) (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ; CAS

No.: 68891-38-3)

Exposure route : Inhalation
Exposure frequency : Long-term (repeated)

Limit value: 175 mg/m³

PNEC

Limit value type : PNEC aquatic, freshwater (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ; CAS

No.: 68891-38-3)

Limit value : 0,24 mg/l

Limit value type: PNEC aquatic, intermittent release (Alcohols, C12-14, ethoxylated, sulfates, sodium

salts; CAS No.: 68891-38-3)

Limit value: 0,071 mg/l

Limit value type: PNEC aquatic, marine water (Alcohols, C12-14, ethoxylated, sulfates, sodium salts;

CAS No.: 68891-38-3)

Limit value: 0,024 mg/l

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Abra-CLEAN

 Revision date :
 25.01.2016
 Version :
 1.0.0

 Print date :
 03.02.2016
 Page :
 5/9

Limit value type : PNEC sediment, freshwater (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ;

CAS No.: 68891-38-3)

Limit value : 5,45 mg/kg

Limit value type: PNEC sediment, marine water (Alcohols, C12-14, ethoxylated, sulfates, sodium salts;

CAS No.: 68891-38-3)

Limit value: 0,545 mg/kg

Limit value type: PNEC sewage treatment plant (STP) (Alcohols, C12-14, ethoxylated, sulfates, sodium

salts; CAS No.: 68891-38-3)

Limit value: 10000 mg/

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection goggles

Required properties

DIN EN 166

Skin protection

Hand protection

Suitable gloves type: Gloves with long cuffs

Suitable material: NBR (Nitrile rubber), 0,4mm, >8h; Butyl caoutchouc, 0,5mm, >8h; FKM (fluoro rubber), 0,7mm,

>8h;

Recommended glove articles: Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

Additional hand protection measures: Check leak tightness/impermeability prior to use.

Remark: Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Protective clothing.

Suitable protective clothing: Chemical protection clothing Chemical resistant safety shoes

Required properties: alkali-resistant.

Recommended protective clothing articles: DIN EN ISO 20345 DIN EN 13034 DIN EN 14605 DIN EN 14404

Remark: Barrier creams are not substitutes for body protection.

Respiratory protection

Usually no personal respirative protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Half-face mask (DIN EN 140) ABEK-P1

Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General health and safety measures

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: viscous
Colour: beige
Odour: fruity

Safety relevant basis data

Freezing point : $(1013 \, \text{hPa})$ < -20 °C Initial boiling point and boiling range : $(1013 \, \text{hPa})$ > 100 °C Decomposition temperature : $(1013 \, \text{hPa})$ not determined

Flash point: > 100 ℃ closed cup

Ignition temperature : not determined

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Abra-CLEAN

 Revision date :
 25.01.2016
 Version :
 1.0.0

 Print date :
 03.02.2016
 Page :
 6 / 9

Sustaining combustion No $\frac{ \text{UN Test L2:Sustained} }{ \text{combustibility test} }$

 Lower explosion limit:
 not determined

 Upper explosion limit:
 not determined

Vapour pressure : $(50 \, ^{\circ}\text{C})$ < 3000 hPa

Density: (20 $^{\circ}$ C) ca. 1,3 g/cm³ Pyknometer

Solvent separation test : $(20~{}^{\circ}{}^{\circ})$ < $3~{}^{\circ}{}^{\circ}$ Water solubility $(20~{}^{\circ}{}^{\circ})$ emulsifiable

pH: ca. 10

log P O/W: not determined

 Odour threshold :
 not determined

 Vapourisation rate :
 not determined

 VOC-FR
 not applicable

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

No hazardous reaction when handled and stored according to provisions.

10.5 Incompatible materials

The product develops hydrogen in an aqueous solution in contact with metals.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter: LD50 (2-AMINOETHANOL ; CAS No. : 141-43-5)

Exposure route : Oral
Species : Rat
Effective dose : 2100 mg/kg

Parameter: LD50 (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ; CAS No. : 68891-38-3)

Exposure route : Oral
Species : Rat
Effective dose : 4100 mg/kg

Acute dermal toxicity

Parameter: LD50 (Alcohols, C12-14, ethoxylated, sulfates, sodium salts; CAS No.: 68891-38-3)

Exposure route: Dermal
Species: Rat
Effective dose: > 2000 mg/kg

Parameter: LD50 (2-AMINOETHANOL; CAS No.: 141-43-5)

Exposure route: Dermal
Species: Rabbit
Effective dose: 1000 mg/kg

Specific symptoms in animal studies

No data available

Irritant and corrosive effects

Assessment/classification

Causes serious eye damage. Causes severe burns.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Abra-CLEAN

 Revision date:
 25.01.2016
 Version:
 1.0.0

 Print date:
 03.02.2016
 Page:
 7/9

Carcinogenicity

No indication of human carcinogenicity.

Germ cell mutagenicity

In vivo mutagenicity

Other information

No experimental indications of in vivo mutagenicity exist.

Human toxicological data

Other information

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

Practical experience/human evidence

No indications of human reproductive toxicity exist.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter: LC50 (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ; CAS No. : 68891-38-3)

Species: Fish
Effective dose: 7,1 mg/l
Exposure time: 96 h

Acute (short-term) daphnia toxicity

Parameter: EC50 (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ; CAS No. : 68891-38-3)

Species: Daphnia
Effective dose: 7,2 mg/l
Exposure time: 48 h

Chronic (long-term) daphnia toxicity

Parameter: NOEC (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ; CAS No. : 68891-38-3)

Species: Daphnia
Effective dose: 0,27 mg/l
Exposure time: 21 Tage

Acute (short-term) algae toxicity

Parameter: IC50 (Alcohols, C12-14, ethoxylated, sulfates, sodium salts ; CAS No. : 68891-38-3)

Species: Algae
Effective dose: 7,5 mg/l
Exposure time: 96 h

Effects in sewage plants

Observe local regulations concerning effluent treatment. Before discharge into sewage plants the product normally needs to be neutralised.

12.2 Persistence and degradability

No data available

Biodegradation

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No data available

12.7 Additional ecotoxicological information

Additional information

The product has not been tested.

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Abra-CLEAN

 Revision date :
 25.01.2016
 Version :
 1.0.0

 Print date :
 03.02.2016
 Page :
 8 / 9

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

Waste code (91/689/EEC): 07 06 04*

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

14.1 UN number

No dangerous goods in sense of this transport regulation.

14.2 UN proper shipping name

No dangerous goods in sense of this transport regulation.

14.3 Transport hazard class(es)

No dangerous goods in sense of this transport regulation.

14.4 Packing group

No dangerous goods in sense of this transport regulation.

14.5 Environmental hazards

No dangerous goods in sense of this transport regulation.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Regulation (EC) No. 648/2004 (Detergents regulation)

National regulations

Observe in addition any national regulations!

Water hazard class (WGK)

Class: 1 (Slightly hazardous to water) Classification according to VwVwS

Other regulations, restrictions and prohibition regulations

VOCV-Regulation (CH)

Maximum VOC content (Switzerland): < 3 Wt % according to VOCV

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 15. Technische Anleitung Luft (TA-Luft)

16.2 Abbreviations and acronyms

None

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: Lithofin Abra-CLEAN

 Revision date :
 25.01.2016
 Version :
 1.0.0

 Print date :
 03.02.2016
 Page :
 9/9

16.3 Key literature references and sources for data

None

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.
H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.