

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 1 / 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Lithofin MN Colour Intensifier

**1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Relevant identified uses**

Mixture Impregnation, contains: organic solvents

**1.3 Supplier (manufacturer/importer/only representative/downstream user/distributor)**

**Distributor :** CDK Stone Pty Ltd  
**Street :** 4-6 Freighter Rd  
**Postal code/city :** AUS-Moorabbin, Victoria 3189  
**Telephone :** +61 3 8552-6000  
**Telefax :** +61 3 8552-6001  
**Contact :** Technical Department  
E-mail:  
  
Emergency telephone number:  
+61 (0)3 8552-6000  
(Only available during office hours)

**Supplier :** Lithofin AG  
**Street :** Heinrich-Otto-Str. 36  
**Postal code/city :** 73240 Wendlingen  
**Telephone :** +49 (0)7024 9403-0  
**Telefax :** +49 (0)7024 9403-40

**1.4 Emergency telephone number**

see section 1.3

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Category 2 ; Toxic to aquatic life with long lasting effects.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

**Additional information**

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

**Remark**

Full text of H- and EUH-phrases: see section 16.

**2.2 Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Environment (GHS09) · Exclamation mark (GHS07)

**Signal word**

Danger

**Hazard components for labelling**

Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 2 / 12

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1)  
ETHYLBENZENE ; CAS No. : 100-41-4

## Hazard statements

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

## Precautionary statements

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P311 Call a POISON CENTER/doctor/....  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/....  
P405 Store locked up.  
P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

## Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

## 2.3 Other hazards

### Adverse physicochemical effects

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

## 2.4 Additional information

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition / information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

Hydrocarbons, C9, aromatics ; REACH registration No. : 01-2119455851-35-xxxx ; EC No. : 918-668-5; CAS No. : (64742-95-6)

Weight fraction :  $\geq 35 - < 40 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; REACH registration No. : 01-2119458049-33-xxxx ; EC No. : 919-446-0; CAS No. : (64742-82-1)

Weight fraction :  $\geq 30 - < 35 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

XYLENE ; REACH registration No. : 01-2119486136-34-xxxx ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction :  $\geq 10 - < 15 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315

ETHYLBENZENE ; EC No. : 202-849-4; CAS No. : 100-41-4

Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H332

#### Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation. < 0,1% Benzene, REG(EC) No 1272/2008, Annex VI; J, P  
Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. Observe risk of aspiration if vomiting occurs.

#### Following inhalation

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 3 / 12

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. In case of respiratory tract irritation, consult a physician.

**In case of skin contact**

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

**After eye contact**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

**After ingestion**

Call a physician immediately. Keep at rest. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

**Self-protection of the first aider**

First aider: Pay attention to self-protection!

**4.2 Most important symptoms and effects, both acute and delayed**

No information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

Water alcohol resistant foam ABC-powder Carbon dioxide (CO<sub>2</sub>) Water spray

**Unsuitable extinguishing media**

Full water jet Strong water jet

**5.2 Special hazards arising from the substance or mixture**

**Hazardous combustion products**

Carbon monoxide. Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

Use suitable breathing apparatus.

**Special protective equipment for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**5.4 Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

**6.2 Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

**6.3 Methods and material for containment and cleaning up**

**For cleaning up**

Suitable material for taking up: Universal binder

**6.4 Reference to other sections**

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

When using do not eat, drink, smoke, sniff.

**Protective measures**

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists

Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 4 / 12

the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

#### Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of ignition. - No smoking. The product is: Combustible

**Fire class :** B

**Shake before use** nein

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.

#### Hints on joint storage

**Storage class (TRGS 510) :** 3

**Protect from frost** nein

**Recommended storage temperature** 5 - 25 °C

#### Further information on storage conditions

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

### 7.3 Specific end use(s)

#### Recommendation

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 100 ppm / 440 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H  
Version : 02.04.2014

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Xylene / Whole blood (B) / End of exposure or end of shift  
Limit value : 1,5 mg/l  
Version : 31.03.2004

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Methylhippuric acid / Urine (U) / End of exposure or end of shift  
Limit value : 2 g/l  
Version : 31.03.2004

Limit value type (country of origin) : STEL ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000

Limit value type (country of origin) : TWA ( EC )  
Limit value : 50 ppm / 221 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 20 ppm / 88 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H, Y  
Version : 02.04.2014

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Ethylbenzene / Whole blood (B) / End of exposure or end of shift  
Limit value : 1 mg/l  
Version : 31.03.2004

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Mandelic acid + Phenylglyoxyl acid / Urine (U) / End of exposure or end of shift  
Limit value : 800 mg/g Kr

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 5 / 12

Version : 31.03.2004  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000

**DNEL/DMEL and PNEC values**

**DNEL/DMEL**

Limit value type : DNEL Consumer (systemic) ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 71 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic) ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 32 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic) ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 11 mg/kg  
Limit value type : DNEL Consumer (systemic) ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 26 mg/kg/d  
Limit value type : DNEL Consumer (systemic) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 108 mg/kg  
Limit value type : DNEL Consumer (systemic) ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Inhalation  
Exposure frequency : Short-term (acute)  
Limit value : 174 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic) ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 14,8 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 14,8 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic) ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Exposure route : Oral  
Exposure frequency : Long-term (repeated)  
Limit value : 26 mg/kg/d  
Limit value type : DNEL Consumer (systemic) ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Exposure route : Oral  
Exposure frequency : Long-term (repeated)  
Limit value : 11 mg/kg  
Limit value type : DNEL Consumer (systemic) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Oral  
Exposure frequency : Long-term (repeated)  
Limit value : 1,6 mg/kg  
Limit value type : DNEL Consumer (systemic) ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 108 mg/kg  
Limit value type : DNEL Consumer (systemic) ( ETHYLBENZENE ; CAS No. : 100-41-4 )

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 6 / 12

Exposure route : Oral  
Exposure frequency : Long-term (repeated)  
Limit value : 1,6 mg/kg  
Limit value type : DNEL worker (systemic) ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Inhalation  
Exposure frequency : Short-term (acute)  
Limit value : 289 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Inhalation  
Exposure frequency : Short-term (acute)  
Limit value : 289 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic) ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 25 mg/kg  
Limit value type : DNEL worker (systemic) ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 330 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic) ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 44 mg/kg/d  
Limit value type : DNEL worker (systemic) ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 150 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 180 mg/kg  
Limit value type : DNEL worker (systemic) ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 77 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic) ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 180 mg/kg  
Limit value type : DNEL worker (systemic) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 77 mg/m<sup>3</sup>

**PNEC**

Limit value type : PNEC aquatic, freshwater ( XYLENE ; CAS No. : 1330-20-7 )  
Limit value : 0,327 mg/l  
Limit value type : PNEC aquatic, intermittent release ( XYLENE ; CAS No. : 1330-20-7 )  
Limit value : 0,327 mg/l  
Limit value type : PNEC aquatic, marine water ( XYLENE ; CAS No. : 1330-20-7 )  
Limit value : 0,327 mg/l  
Limit value type : PNEC sediment, freshwater ( XYLENE ; CAS No. : 1330-20-7 )  
Limit value : 12,46 mg/kg  
Limit value type : PNEC sediment, marine water ( XYLENE ; CAS No. : 1330-20-7 )  
Limit value : 12,46 mg/kg  
Limit value type : PNEC sewage treatment plant (STP) ( XYLENE ; CAS No. : 1330-20-7 )  
Limit value : 6,58 mg/l

**8.2 Exposure controls**

**Personal protection equipment**

**Eye/face protection**

**Suitable eye protection**

Eye glasses with side protection goggles

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 7 / 12

## Required properties

DIN EN 166

## Skin protection

### Hand protection

**Suitable gloves type :** Gloves with long cuffs

**Suitable material :** Data apply to the main component. FKM (fluoro rubber), 0,7mm, >8h;

**Recommended glove articles :** Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

**Additional hand protection measures :** Check leak tightness/impermeability prior to use.

**Remark :** Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### Body protection

Protective clothing.

**Suitable protective clothing :** Chemical protection clothing Chemical resistant safety shoes

**Required properties :** antistatic.

**Recommended protective clothing articles :** DIN EN ISO 20345 DIN EN 13034 DIN EN 14605 DIN EN 14404

**Remark :** Barrier creams are not substitutes for body protection.

## Respiratory protection

Usually no personal respirative protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

### Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Half-face mask (DIN EN 140) ABEK-P1

### Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

## General health and safety measures

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Appearance :** liquid

**Colour :** colourless

**Odour :** solvent

### Safety relevant basis data

<b>Freezing point :</b>	( 1013 hPa )	<	-13	°C	
<b>Initial boiling point and boiling range :</b>	( 1013 hPa )	ca.	158	°C	
<b>Decomposition temperature :</b>	( 1013 hPa )		not determined		
<b>Flash point :</b>		ca.	36	°C	closed cup
<b>Ignition temperature :</b>			not determined		
<b>Sustaining combustion</b>			Yes		UN Test L2:Sustained combustibility test
<b>Lower explosion limit :</b>			not determined		
<b>Upper explosion limit :</b>			not determined		
<b>Vapour pressure :</b>	( 50 °C )	<	3000	hPa	
<b>Density :</b>	( 20 °C )	ca.	0,9	g/cm <sup>3</sup>	Pyknometer
<b>Solvent separation test :</b>	( 20 °C )	<	3	%	
<b>Water solubility</b>	( 20 °C )		hydrolysed		
<b>pH :</b>			not applicable		
<b>log P O/W :</b>			not determined		
<b>Flow time :</b>	( 23 °C )	ca.	14	s	ISO cup 4 mm
<b>Odour threshold :</b>			not determined		
<b>Vapourisation rate :</b>			not determined		
<b>VOC-FR</b>			A+		

### 9.2 Other information

None

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 8 / 12

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4 Conditions to avoid

No hazardous reaction when handled and stored according to provisions.

### 10.5 Incompatible materials

No data available

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute effects

##### Acute oral toxicity

Parameter :	LD50 ( XYLENE ; CAS No. : 1330-20-7 )
Exposure route :	Oral
Species :	Rat
Effective dose :	8700 mg/kg
Parameter :	LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )
Exposure route :	Oral
Species :	Rat
Effective dose :	3500 mg/kg
Parameter :	LD50 ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 15000 mg/kg
Method :	OECD 401
Parameter :	LD50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 - 5000 mg/kg

##### Acute dermal toxicity

Parameter :	LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	15354 mg/kg
Parameter :	LD50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg
Parameter :	LD50 ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )
Exposure route :	Dermal
Species :	Rat
Effective dose :	3400 mg/kg
Method :	OECD 402
Parameter :	LD50 ( XYLENE ; CAS No. : 1330-20-7 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg

##### Acute inhalation toxicity

Parameter :	LC50 ( XYLENE ; CAS No. : 1330-20-7 )
Exposure route :	Inhalation



**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 9 / 12

Species : Rat  
Effective dose : 6350 mg/l  
Parameter : LC50 ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 13100 mg/l  
Method : OECD 403  
Parameter : LC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Inhalation  
Species : Mouse  
Effective dose : 35,5 mg/l

#### Specific symptoms in animal studies

No data available

#### Irritant and corrosive effects

##### Assessment/classification

Repeated exposure may cause skin dryness or cracking.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

##### Carcinogenicity

No indication of human carcinogenicity.

##### Germ cell mutagenicity

##### In vivo mutagenicity

##### Other information

No experimental indications of in vivo mutagenicity exist.

##### Human toxicological data

##### Other information

No indications of human germ cell mutagenicity exist.

##### Reproductive toxicity

##### Practical experience/human evidence

No indications of human reproductive toxicity exist.

##### Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Fish  
Effective dose : 7,6 mg/l  
Exposure time : 96 h  
Parameter : LC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Species : Fish  
Effective dose : 94,44 mg/l  
Exposure time : 96 h  
Parameter : LC50 ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Species : Fish  
Effective dose : > 10 mg/l  
Exposure time : 96 h  
Method : OECD 203  
Parameter : LC50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Species : Fish  
Effective dose : > 1 - 10 mg/l

##### Chronic (long-term) fish toxicity

Parameter : NOEC ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Fish  
Effective dose : > 1 - 10 mg/l

##### Acute (short-term) daphnia toxicity

Parameter : EC50 ( XYLENE ; CAS No. : 1330-20-7 )

**Trade name : Lithofin MN Colour Intensifier**

Revision date : 26.01.2016  
Print date : 02.02.2016

Version : 1.0.0  
Page : 10 / 12

Species : Daphnia  
Effective dose : 3,82 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Species : Daphnia  
Effective dose : 2,1 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Species : Daphnia  
Effective dose : > 10 mg/l  
Exposure time : 48 h  
Method : OECD 202  
Parameter : EC50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Species : Daphnia  
Effective dose : > 1 - 10 mg/l

**Chronic (long-term) daphnia toxicity**

Parameter : NOEC ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Species : Daphnia  
Effective dose : 0,097 mg/l  
Exposure time : 21 Tage

**Acute (short-term) algae toxicity**

Parameter : IC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Algae  
Effective dose : 4,7 mg/l  
Exposure time : 72 h  
Parameter : IC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Species : Algae  
Effective dose : 4,6 mg/l  
Exposure time : 72 h  
Parameter : IC50 ( Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; CAS No. : (64742-82-1) )  
Species : Algae  
Effective dose : 4,6 mg/l  
Exposure time : 72 h  
Parameter : IC50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Species : Algae  
Effective dose : > 1 - 10 mg/l

**Effects in sewage plants**

Observe local regulations concerning effluent treatment.

**12.2 Persistence and degradability**

No data available

**Biodegradation**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6 Other adverse effects**

No data available

**12.7 Additional ecotoxicological information**

**Additional information**

The product has not been tested.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Dispose according to legislation.

**Trade name :** Lithofin MN Colour Intensifier

Revision date : 26.01.2016  
Print date : 02.02.2016

Version : 1.0.0  
Page : 11 / 12

### Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

Waste code (91/689/EEC) : 07 01 04\*

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

### 13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

## SECTION 14: Transport information

### 14.1 UN number

UN 1993

### 14.2 UN proper shipping name

Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

Sea transport (IMDG)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

### 14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3  
Classification code : F1  
Hazard identification number (Kemler No.) : 30  
Tunnel restriction code : D/E  
Special provisions : 640E · LQ 5 I · E 1  
Hazard label(s) : 3 / N

Sea transport (IMDG)

Class(es) : 3  
EmS-No. : F-E / S-E  
Special provisions : LQ 5 I · E 1  
Hazard label(s) : 3 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3  
Special provisions : E 1  
Hazard label(s) : 3

### 14.4 Packing group

III

### 14.5 Environmental hazards

Land transport (ADR/RID) : Yes

Sea transport (IMDG) : Yes (P)

Air transport (ICAO-TI / IATA-DGR) : Yes

### 14.6 Special precautions for user

None

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Observe in addition any national regulations!

Water hazard class (WGK)

Class : 2 (Hazardous to water) Classification according to VwVwS

Other regulations, restrictions and prohibition regulations

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Colour Intensifier

**Revision date :** 26.01.2016  
**Print date :** 02.02.2016

**Version :** 1.0.0  
**Page :** 12 / 12

**VOCV-Regulation (CH)**

Maximum VOC content (Switzerland) : 86,8 Wt % according to VOCV

**15.2 Chemical Safety Assessment**

No information available.

**SECTION 16: Other information**

**16.1 Indication of changes**

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients

**16.2 Abbreviations and acronyms**

None

**16.3 Key literature references and sources for data**

None

**16.4 Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]**

No information available.

**16.5 Relevant H- and EUH-phrases (Number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

**16.6 Training advice**

None

**16.7 Additional information**

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.