

---

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

### 1.1 Product identifier

**Product name** RIVO 50 PART A

**Synonyms**

### 1.2 Uses and uses advised against

**Uses** EPOXY RESIN • TWO COMPONENT EPOXY SYSTEM

### 1.3 Details of the supplier of the product

**Supplier name** CDK STONE PTY LTD

**Address** 4 - 6 Freighter Rd, Moorabbin, VIC, 3189, AUSTRALIA

**Telephone** (03) 8552 6000

**Fax** (03) 8552 6001

**Email** [help@cdkstone.com.au](mailto:help@cdkstone.com.au)

**Website** <http://www.cdkstone.com.au>

### 1.4 Emergency telephone numbers

**Emergency** 13 11 26

---

## 2. HAZARDS IDENTIFICATION

---

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### Physical Hazards

Not classified as a Physical Hazard

#### Health Hazards

Skin Corrosion/Irritation: Category 2

Skin Sensitisation: Category 1

Serious Eye Damage / Eye Irritation: Category 2A

Germ Cell Mutagenicity: Category 2

#### Environmental Hazards

Aquatic Toxicity (Chronic): Category 2

### 2.2 GHS Label elements

**Signal word** WARNING

**Pictograms**



#### Hazard statements

|      |  |
|------|--|
| H315 | Causes skin irritation.                          |
| H317 | May cause an allergic skin reaction.             |
| H319 | Causes serious eye irritation.                   |
| H341 | Suspected of causing genetic defects.            |
| H411 | Toxic to aquatic life with long lasting effects. |

**PRODUCT NAME RIVO 50 PART A****Prevention statements**

|      |  |
|------|--|
| P201 | Obtain special instructions before use.                                    |
| P202 | Do not handle until all safety precautions have been read and understood.  |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray.                          |
| P264 | Wash thoroughly after handling.  |
| P272 | Contaminated work clothing should not be allowed out of the workplace.     |
| P273 | Avoid release to the environment.  |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |

**Response statements**

|                    |  |
|--------------------|--|
| P302 + P352        | IF ON SKIN: Wash with plenty of water.   |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308 + P313        | IF exposed or concerned: Get medical advice/ attention.  |
| P321               | Specific treatment is advised - see first aid instructions.  |
| P362 + P364        | Take off contaminated clothing and wash it before reuse.   |
| P391               | Collect spillage.  |

**Storage statements**

|      |                  |
|------|------------------|
| P405 | Store locked up. |
|------|------------------|

**Disposal statements**

|      |  |
|------|--|
| P501 | Dispose of contents/container in accordance with relevant regulations. |
|------|--|

**2.3 Other hazards**

No information provided.

---

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**

---

**3.1 Substances / Mixtures**

| Ingredient  | CAS Number | EC Number | Content    |
|---|------------|-----------|------------|
| REACTION PRODUCT:<br>BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN<br>(NUMBER AVERAGE MOLECULAR WEIGHT $\leq$ 700) | 25068-38-6 | 500-033-5 | 57 to <59% |
| GLYCIDYL-2-METHYLPHENYL ETHER   | 2210-79-9  | 218-645-3 | 4.5 to <5% |
| ADDITIVE(S)   | -          | -         | Remainder  |

---

**4. FIRST AID MEASURES**

---

**4.1 Description of first aid measures**

|                             |  |
|-----------------------------|--|
| <b>Eye</b>                  | If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.                       |
| <b>Inhalation</b>           | If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing. |
| <b>Skin</b>                 | If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.       |
| <b>Ingestion</b>            | For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.   |
| <b>First aid facilities</b> | Eye wash facilities and safety shower should be available.   |

**4.2 Most important symptoms and effects, both acute and delayed**

Irritating to the eyes and skin. May cause sensitisation by skin contact.

**4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

---

**5. FIRE FIGHTING MEASURES**

---

**5.1 Extinguishing media**

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

**5.2 Special hazards arising from the substance or mixture**

Combustible. May evolve toxic gases (carbon/ nitrogen oxides, hydrocarbons) when heated to decomposition.

### **5.3 Advice for firefighters**

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

### **5.4 Hazchem code**

- 3Z
- 3 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, normal foam can be used.
- Z Wear full fire kit and breathing apparatus. Contain spill and run-off.

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

### **6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

### **6.2 Environmental precautions**

Prevent product from entering drains and waterways.

### **6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

### **6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

## **7. HANDLING AND STORAGE**

---

### **7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### **7.2 Conditions for safe storage, including any incompatibilities**

Store tightly sealed in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be bunded and have appropriate fire protection and ventilation systems.

### **7.3 Specific end uses**

No information provided.

---

## **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

### **8.1 Control parameters**

#### **Exposure standards**

No exposure standards have been entered for this product.

#### **Biological limits**

No biological limit values have been entered for this product.

### **8.2 Exposure controls**

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

**PRODUCT NAME RIVO 50 PART A**

**PPE**

|                    |   |
|--------------------|---|
| <b>Eye / Face</b>  | Wear splash-proof goggles.  |
| <b>Hands</b>       | Wear PVA or Viton® or nitrile gloves.   |
| <b>Body</b>        | Wear coveralls. If spraying, with prolonged use, or if in confined areas, wear impervious coveralls.  |
| <b>Respiratory</b> | Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. If sanding dry product, wear a Class P1 (Particulate) respirator. |



---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

**9.1 Information on basic physical and chemical properties**

|                                  |                      |
|----------------------------------|----------------------|
| <b>Appearance</b>                | COLOURED PASTE       |
| <b>Odour</b>                     | TYPICAL ODOUR        |
| <b>Flammability</b>              | CLASS C2 COMBUSTIBLE |
| <b>Flash point</b>               | 160°C                |
| <b>Boiling point</b>             | NOT AVAILABLE        |
| <b>Melting point</b>             | NOT AVAILABLE        |
| <b>Evaporation rate</b>          | NOT AVAILABLE        |
| <b>pH</b>                        | NOT AVAILABLE        |
| <b>Vapour density</b>            | NOT AVAILABLE        |
| <b>Relative density</b>          | 1.2                  |
| <b>Solubility (water)</b>        | INSOLUBLE            |
| <b>Vapour pressure</b>           | NOT AVAILABLE        |
| <b>Upper explosion limit</b>     | NOT AVAILABLE        |
| <b>Lower explosion limit</b>     | NOT AVAILABLE        |
| <b>Partition coefficient</b>     | NOT AVAILABLE        |
| <b>Autoignition temperature</b>  | NOT AVAILABLE        |
| <b>Decomposition temperature</b> | NOT AVAILABLE        |
| <b>Viscosity</b>                 | NOT AVAILABLE        |
| <b>Explosive properties</b>      | NOT AVAILABLE        |
| <b>Oxidising properties</b>      | NOT AVAILABLE        |
| <b>Odour threshold</b>           | NOT AVAILABLE        |

---

**10. STABILITY AND REACTIVITY**

---

**10.1 Reactivity**

Carefully review all information provided in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation is not expected to occur.

**10.4 Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

**10.6 Hazardous decomposition products**

May evolve toxic gases (carbon/ nitrogen oxides, hydrocarbons) when heated to decomposition.

---

**11. TOXICOLOGICAL INFORMATION**

---

**11.1 Information on toxicological effects**

**Acute toxicity** Acute oral exposure may result in irritation of the mouth, throat, oesophagus and gastrointestinal tract.

**Information available for the ingredients:**

| Ingredient  | Oral LD50        | Dermal LD50        | Inhalation LC50 |
|---|------------------|--------------------|-----------------|
| REACTION PRODUCT:<br>BISPHENOL-A-(EPICHLORHYDRIN) EPOXY<br>RESIN (NUMBER AVERAGE MOLECULAR<br>WEIGHT ≤ 700) | > 15 g/kg (rat)  | > 23 g/kg (rabbit) | --              |
| GLYCIDYL-2-METHYLPHENYL ETHER   | 4000 mg/kg (rat) | --                 | --              |

**Skin** Contact may result in irritation, redness, rash and dermatitis.  
**Eye** Contact may result in irritation, lacrimation, pain and redness.  
**Sensitisation** Epoxy resins may cause allergic skin reactions. Insufficient data for classification as a respiratory sensitiser.  
**Mutagenicity** Suspected of causing genetic defects.  
**Carcinogenicity** Not classified as a carcinogen.  
**Reproductive** Not classified as a reproductive toxin.  
**STOT - single exposure** Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in dizziness, drowsiness and breathing difficulties.  
**STOT - repeated exposure** Not classified as causing organ damage from repeated exposure.  
**Aspiration** Not classified as causing aspiration.

**12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

Toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

No information provided.

**12.3 Bioaccumulative potential**

No information provided.

**12.4 Mobility in soil**

No information provided.

**12.5 Other adverse effects**

No information provided.

**13. DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

**Waste disposal** Mix components together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer/supplier for additional information (if required). Prevent contamination of drains and waterways as environmental damage may result.

**Legislation** Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION**

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



|                             | LAND TRANSPORT (ADG)  | SEA TRANSPORT (IMDG / IMO)  | AIR TRANSPORT (IATA / ICAO)   |
|-----------------------------|---|---|---|
| 14.1 UN Number              | 3082  | 3082  | 3082  |
| 14.2 Proper Shipping Name   | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains reaction product: bisphenol a-(epichlorhydrin), trimethylolpropane triacrylate) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains reaction product: bisphenol a-(epichlorhydrin), trimethylolpropane triacrylate) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains reaction product: bisphenol a-(epichlorhydrin), trimethylolpropane triacrylate) |
| 14.3 Transport hazard class | 9   | 9   | 9   |
| 14.4 Packing Group          | III   | III   | III   |

**14.5 Environmental hazards**

Marine Pollutant.

**14.6 Special precautions for user**

Hazchem code ●3Z  
 GTEPG 9C1  
 EmS F-A, S-F

**Other information** The environmentally hazardous substance mark is not required when transported in packages of less than 5 kg/L (UN Model Regulations: Special Provision 375; IATA: Special Provision A197; IMDG: Special Provision 969) or less than 500 kg/L by Australian Road and Rail.

**15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule** Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings** **AUSTRALIA: AIC (Australian Inventory of Industrial Chemicals)**  
 All components are listed on AIC, or are exempt.

**16. OTHER INFORMATION**

**Additional information** WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (e.g. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

EPOXY - PHENOXY RESINS AND POLYURETHANES: Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered non toxic.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:  
 The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Abbreviations**

|                   |   |
|-------------------|---|
| ACGIH             | American Conference of Governmental Industrial Hygienists                                       |
| CAS #             | Chemical Abstract Service number - used to uniquely identify chemical compounds                 |
| CNS               | Central Nervous System  |
| EC No.            | EC No - European Community Number   |
| EMS               | Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)                   |
| GHS               | Globally Harmonized System  |
| GTEPG             | Group Text Emergency Procedure Guide  |
| IARC              | International Agency for Research on Cancer   |
| LC50              | Lethal Concentration, 50% / Median Lethal Concentration   |
| LD50              | Lethal Dose, 50% / Median Lethal Dose   |
| mg/m <sup>3</sup> | Milligrams per Cubic Metre  |
| OEL               | Occupational Exposure Limit   |
| pH                | relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). |
| ppm               | Parts Per Million   |
| STEL              | Short-Term Exposure Limit   |
| STOT-RE           | Specific target organ toxicity (repeated exposure)  |
| STOT-SE           | Specific target organ toxicity (single exposure)  |
| SUSMP             | Standard for the Uniform Scheduling of Medicines and Poisons                                    |
| SWA               | Safe Work Australia   |
| TLV               | Threshold Limit Value   |
| TWA               | Time Weighted Average   |

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**